

In the Claims

Claims 1-9 are pending and are listed below:

1. (Original) An electronic display device comprising:

5 a housing;
a display area provided within the housing to display content for a user;
memory within the housing to hold data that is to be rendered into user-viewable content;

an electrophotographic assembly within the housing configured to
10 electrophotographically render user-viewable content from the data that is held in the memory;

a loop of material disposed proximate the electrophotographic assembly and configured to receive electrophotographically rendered content and present the content for user viewing within the display area; and

15 a control area on the housing comprising one or more user-engagable structures to permit a user to interact with the device, the control area being positioned on the housing to accommodate one-handed use of the device.

2. (Original) The electronic display device of claim 1, wherein the
20 loop of material comprises a dielectric material.

3. (Original) The electronic display device of claim 1 further comprising a power source internally of the housing.

25 4. (Original) The electronic display device of claim 3, wherein the power source comprises one or more batteries.

5. (Original) An electronic display device comprising:
a housing;
a display area provided within the housing to display content for a user;
memory within the housing to hold data that is to be rendered into user-
5 viewable content;

an electrophotographic assembly within the housing configured to
electrophotographically render user-viewable content from the data that is held
in the memory, the content being renderable by the assembly at at least 300 dpi;

a loop of material disposed proximate the electrophotographic assembly
10 and configured to receive electrophotographically rendered content and present
the content for user viewing within the display area; and

a control area on the housing comprising one or more user-engagable
structures to permit a user to interact with the device, the control area being
positioned on the housing to accommodate one-handed use of the device.

15

6. (Original) The electronic display device of claim 5, wherein the
assembly is configured to render the content at 600 dpi.

7. (Original) The electronic display device of claim 5, wherein the
20 assembly is configured to render the content at 600 dpi, and the device weights
no more than two pounds.

8. (Original) An electronic display device comprising:
a housing;
25 a display area provided within the housing to display content for a user;
memory within the housing to hold data that is to be rendered into user-
viewable content;

a print media within the housing and configured to display, with toner, user-viewable content for a user;

a toner shuttling system within the housing configured to shuttle toner between different locations within the housing from which the toner can be
5 used and reused; and

a control area on the housing comprising one or more user-engagable structures to permit a user to interact with the device, the control area being positioned on the housing to accommodate one-handed use of the device.

10 9. (Original) The electronic display device of claim 8 further comprising an exposure station within the housing positioned to expose the loop of material so that toner can be applied and retained thereon.